

PB-240 304

CANANDAIGUA LAKE, ONTARIO AND YATES  
COUNTIES, NEW YORK

Pacific Northwest Environmental  
Research Laboratory

Prepared for:

National Environmental Research Center  
New York State Department of Environmental  
Conservation  
New York National Guard

November 1974

DISTRIBUTED BY:

**NTIS**

National Technical Information Service  
U. S. DEPARTMENT OF COMMERCE

**TECHNICAL REPORT DATA**  
(Please read instructions on the reverse before completion)

|                                                                                                                                                                                                                                                                                                                                                                                                                                 |  |                                  |  |                                                              |  |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----------------------------------|--|--------------------------------------------------------------|--|
| 1. REPORT NO.                                                                                                                                                                                                                                                                                                                                                                                                                   |  | 2.                               |  | PB 240 304                                                   |  |
| 4. TITLE AND SUBTITLE<br>Report on Canandaigua Lake, Ontario and Yates Counties,<br>New York                                                                                                                                                                                                                                                                                                                                    |  |                                  |  | 5. REPORT DATE<br>Prepared November 1974                     |  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                 |  |                                  |  | 6. PERFORMING ORGANIZATION CODE                              |  |
| 7. AUTHOR(S)<br>Anonymous (National Eutrophication Survey Staff)                                                                                                                                                                                                                                                                                                                                                                |  |                                  |  | 8. PERFORMING ORGANIZATION REPORT NO.<br>Working Paper # 149 |  |
| 9. PERFORMING ORGANIZATION NAME AND ADDRESS<br>Pacific Northwest Environmental Research Laboratory<br>U.S. Environmental Protection Agency<br>200 S. W. 35th St.<br>Corvallis, Oregon 97330                                                                                                                                                                                                                                     |  |                                  |  | 10. PROGRAM ELEMENT NO.<br>18A029                            |  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                 |  |                                  |  | 11. CONTRACT/GRANT NO.                                       |  |
| 12. SPONSORING AGENCY NAME AND ADDRESS<br>Office of Research and Development<br>U.S. Environmental Protection Agency<br>401 M Street, S. W.<br>Washington, DC 20460                                                                                                                                                                                                                                                             |  |                                  |  | 13. TYPE OF REPORT AND PERIOD COVERED<br>Final - 1972        |  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                 |  |                                  |  | 14. SPONSORING AGENCY CODE                                   |  |
| 15. SUPPLEMENTARY NOTES<br>Prepared in cooperation with the U.S. Environmental Protection Agency, National<br>Environmental Research Center, Las Vegas, Nevada 89114                                                                                                                                                                                                                                                            |  |                                  |  |                                                              |  |
| 16. ABSTRACT<br>Annual total phosphorus and total nitrogen loadings to the lake were estimated and<br>subdivided according to either point or non-point source origin. An assessment of<br>the lake's trophic condition and limiting nutrient is also provided. All data<br>collected by the U.S.E.P.A. National Eutrophication Survey during the one year<br>study of the lake and its tributaries are included in the report. |  |                                  |  |                                                              |  |
| <p align="center">Reproduced by<br/> <b>NATIONAL TECHNICAL<br/>         INFORMATION SERVICE</b><br/>         U.S. Department of Commerce<br/>         Springfield, VA. 22151</p>                                                                                                                                                                                                                                                |  |                                  |  |                                                              |  |
| 17. KEY WORDS AND DOCUMENT ANALYSIS                                                                                                                                                                                                                                                                                                                                                                                             |  |                                  |  |                                                              |  |
| a. DESCRIPTORS                                                                                                                                                                                                                                                                                                                                                                                                                  |  | b. IDENTIFIERS/OPEN ENDED TERMS  |  | c. COSATI Field/Group                                        |  |
| eutrophication<br>lakes<br>nutrients<br>phosphorus<br>nitrogen<br>loading                                                                                                                                                                                                                                                                                                                                                       |  |                                  |  | 05B<br>05C                                                   |  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                 |  |                                  |  | <b>PRICES SUBJECT TO CHANGE</b>                              |  |
| 18. DISTRIBUTION STATEMENT<br>Release unlimited                                                                                                                                                                                                                                                                                                                                                                                 |  | 19. SECURITY CLASS (This Report) |  | 21. NO. OF PAGES<br>41                                       |  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                 |  | 20. SECURITY CLASS (This page)   |  | 22. PRICE<br>3.75-2.25                                       |  |

REPORT  
ON  
CANANDAIGUA LAKE  
ONTARIO AND YATES COUNTIES  
NEW YORK  
EPA REGION II  
WORKING PAPER No. 149

WITH THE COOPERATION OF THE  
NEW YORK STATE DEPARTMENT OF ENVIRONMENTAL CONSERVATION  
AND THE  
NEW YORK NATIONAL GUARD  
NOVEMBER, 1974

## CONTENTS

|                                             | <u>Page</u> |
|---------------------------------------------|-------------|
| Foreword                                    | 11          |
| List of New York Study Lakes                | 1v          |
| Lake and Drainage Area Map                  | v           |
| <u>Sections</u>                             |             |
| I. Conclusions                              | 1           |
| II. Lake and Drainage Basin Characteristics | 3           |
| III. Lake Water Quality Summary             | 4           |
| IV. Nutrient Loadings                       | 9           |
| V. Literature Reviewed                      | 14          |
| VI. Appendices                              | 15          |

## FOREWORD

The National Eutrophication Survey was initiated in 1972 in response to an Administration commitment to investigate the nationwide threat of accelerated eutrophication to fresh water lakes and reservoirs.

### OBJECTIVES

The Survey was designed to develop, in conjunction with state environmental agencies, information on nutrient sources, concentrations, and impact on selected freshwater lakes as a basis for formulating comprehensive and coordinated national, regional, and state management practices relating to point-source discharge reduction and non-point source pollution abatement in lake watersheds.

### ANALYTIC APPROACH

The mathematical and statistical procedures selected for the Survey's eutrophication analysis are based on related concepts that:

- a. A generalized representation or model relating sources, concentrations, and impacts can be constructed.
- b. By applying measurements of relevant parameters associated with lake degradation, the generalized model can be transformed into an operational representation of a lake, its drainage basin, and related nutrients.
- c. With such a transformation, an assessment of the potential for eutrophication control can be made.

### LAKE ANALYSIS

In this report, the first stage of evaluation of lake and watershed data collected from the study lake and its drainage basin is documented. The report is formatted to provide state environmental agencies with specific information for basin planning [§303(e)], water quality criteria/standards review [§303(c)], clean lakes [§314(a,b)], and water quality monitoring [§106 and §305(b)] activities mandated by the Federal Water Pollution Control Act Amendments of 1972.

Beyond the single lake analysis, broader based correlations between nutrient concentrations (and loading) and trophic condition are being made to advance the rationale and data base for refinement of nutrient water quality criteria for the Nation's fresh water lakes. Likewise, multivariate evaluations for the relationships between land use, nutrient export, and trophic condition, by lake class or use, are being developed to assist in the formulation of planning guidelines and policies by EPA and to augment plans implementation by the states.

#### ACKNOWLEDGMENT

The staff of the National Eutrophication Survey (Office of Research & Development, U. S. Environmental Protection Agency) expresses sincere appreciation to the New York Department of Environmental Conservation for professional involvement and to the New York National Guard for conducting the tributary sampling phase of the Survey.

Henry L. Diamond, Commissioner of the New York Department of Environmental Conservation, and Leo J. Hetling, Director, and Italo G. Carcich, Senior Sanitary Engineer, Environmental Quality Research, Department of Environmental Conservation, provided invaluable lake documentation and counsel during the Survey.

Major General John C. Baker, the Adjutant General of New York, and Project Officer Lieutenant Colonel Fred Peters, who directed the volunteer efforts of the New York National Guardsmen, are also gratefully acknowledged for their assistance to the Survey.

## NATIONAL EUTROPHICATION SURVEY

## STUDY LAKES

STATE OF NEW YORKLAKE NAMECOUNTY

Allegheny Reservoir

Cattaraugus, NY; McLean,

Warren, PA

St. Lawrence

Black

Ontario

Canandaigua

Delaware

Cannonsville

St. Lawrence

Carry Falls

Chautauqua

Cassadaga

Seneca, Tompkins

Cayuga

Clinton, Essex, NY; Addison,

Champlain

Chittenden, Franklin, VT

Chautauqua

Chautauqua

Livingston

Conesus

Cayuga, Onondaga

Cross

Otsego

Goodyear

Sullivan

Huntington

Ontario

Keuka

Hamilton

Long

Franklin

Lower St. Regis

Cayuga

Otter

Cayuga

Owasco

Franklin

Raquette Pond

Saratoga

Round

Fulton, Saratoga

Sacandaga Res.

Saratoga

Saratoga

Essex, Warren

Schroon

Seneca, Schryler, Yates


Seneca

Sullivan

Swan

Sullivan

Swinging Bridge Res.



## CANANDAIGUA LAKE

STORET NO. 3604

### I. CONCLUSIONS

#### A. Trophic Condition:

Survey data and data of other studies indicate Canandaigua Lake is oligotrophic. Of the 26 New York lakes sampled in the fall when essentially all were well-mixed, only one (Schroon Lake) had less mean total phosphorus, four had less mean dissolved phosphorus, but 16 had less mean inorganic nitrogen. For all sampling data, four lakes had less mean chlorophyll a, but none had a greater Secchi disc transparency. Only a slight depression of dissolved oxygen with depth (to 218 feet) was noted.

Birge and Juday (1914), in their classical study of the Finger Lakes, reported a Secchi disc transparency of 3.7 meters for the month of August. Survey data for the month of July indicate a mean Secchi disc transparency of 3.0 meters for all stations, thus there is some indication of change in transparency.

#### B. Rate-Limiting Nutrient:

The algal assay results indicate Canandaigua Lake was phosphorus limited at the time the sample was collected (October, 1972).

The lake data also indicate phosphorus limitation at all sampling times; i.e., nitrogen to phosphorus ratios were greater than 14 to 1, and phosphorus limitation would be expected.

1,

### C. Nutrient Controllability:

1. Point sources--During the sampling year, Canandaigua Lake received a total phosphorus load at a rate a little less than that proposed by Vollenweider (in press) as "permissible"; i.e., an oligotrophic rate (see page 13). Of that load, it is estimated that point sources (including shoreline septic tanks) contributed about 46%. The state-wide ban of phosphates in detergents may be expected to reduce phosphorus loading from wastewater treatment plants about 50% (after existing supplies of phosphate detergent are exhausted). The ban on phosphate detergents, together with the existing favorable loading rate, should preserve the oligotrophic condition of Canandaigua Lake.

2. Non-point sources (see page 13)--The non-point phosphorus exports of the Canandaigua Lake tributaries compare very favorably to the exports of unimpacted streams studied elsewhere in New York (e.g., Keuka Lake\*). However, the phosphorus export of the unnamed stream (C-1) was appreciably greater than the other streams and may have resulted from septic tanks at the community of Vine Valley (see map, page vi).

In all, it is estimated that non-point sources contributed about 54% of the total phosphorus load to the lake during the sampling year.

---

\* Working Paper No. 160.

## II. LAKE AND DRAINAGE BASIN CHARACTERISTICS

### A. Lake Morphometry<sup>†</sup>:

1. Surface area: 10,624 acres.
2. Mean depth: 128 feet.
3. Maximum depth: 274 feet.
4. Volume: 1,359,872 acre/feet.
5. Mean hydraulic retention time: 15 years.

### B. Tributary and Outlet: (See Appendix A for flow data)

#### 1. Tributaries -

| <u>Name</u>                                 | <u>Drainage area*</u> | <u>Mean flow*</u> |
|---------------------------------------------|-----------------------|-------------------|
| West River                                  | 29.3 mi <sup>2</sup>  | 17.1 cfs          |
| Seneca Point Gully                          | 4.4 mi <sup>2</sup>   | 2.6 cfs           |
| Unnamed Stream (C-1)                        | 4.7 mi <sup>2</sup>   | 2.7 cfs           |
| Barnes Gully                                | 1.3 mi <sup>2</sup>   | 0.7 cfs           |
| Menteth Gully                               | 6.0 mi <sup>2</sup>   | 3.6 cfs           |
| Naples Creek                                | 47.7 mi <sup>2</sup>  | 49.1 cfs          |
| Minor tributaries &<br>immediate drainage - | 74.0 mi <sup>2</sup>  | 52.3 cfs          |
| Totals                                      | 167.4 mi <sup>2</sup> | 128.1 cfs         |

#### 2. Outlet -

|                                      |                          |             |
|--------------------------------------|--------------------------|-------------|
| Feeder Canal & Canandaigua<br>outlet | 184.0 mi <sup>2</sup> ** | 128.1 cfs** |
|--------------------------------------|--------------------------|-------------|

### C. Precipitation\*\*\*:

1. Year of sampling: 29.2 inches.
2. Mean annual: 22.8 inches.

<sup>†</sup> Gelser, 1974.

\* Drainage areas are accurate within  $\pm 5\%$ , except for small basins ( $\pm 10\%$ ); mean daily flows are accurate within  $\pm 5$  to  $25\%$ ; and normalized mean monthly flows are accurate within  $\pm 15\%$ .

\*\* Includes area of lake; outflow adjusted to equal sum of inflows.

\*\*\* See Working Paper No. 1, "Survey Methods".

### III. LAKE WATER QUALITY SUMMARY

Canandaigua Lake was sampled three times during the open-water season of 1972 by means of a pontoon-equipped Huey helicopter. Each time, samples for physical and chemical parameters were collected from three stations on the lake and from a number of depths at each station (see map, page v). During each visit a single depth-integrated (15 feet or near bottom to surface) sample was composited from the three stations for phytoplankton identification and enumeration; and during the last visit, a single five-gallon depth-integrated sample was composited for algal assays. Also each time, a depth-integrated sample was collected from each of the stations for chlorophyll a analysis. The maximum depths sampled were 15 feet at station 1, 218 feet at station 2, and 156 feet at station 3.

The results obtained are presented in full in Appendix B, and the data for the fall sampling period, when the lake was essentially well-mixed, are summarized below. Note, however, the Secchi disc summary is based on all values.

For differences in the various parameters at the other sampling times, refer to Appendix B.

## A. Physical and chemical characteristics:

FALL VALUES

(10/14/72)

| <u>Parameter</u>                         | <u>Minimum</u> | <u>Mean</u> | <u>Median</u> | <u>Maximum</u> |
|------------------------------------------|----------------|-------------|---------------|----------------|
| Temperature (Cent.)                      | 4.5            | 9.8         | 12.5          | 13.8           |
| Dissolved oxygen (mg/l)                  | 8.0            | 9.4         | 9.6           | 10.6           |
| Conductivity ( $\mu$ mhos)               | 304            | 319         | 320           | 340            |
| pH (units)                               | 7.6            | 8.0         | 8.1           | 8.2            |
| Alkalinity (mg/l)                        | 83             | 107         | 108           | 120            |
| Total P (mg/l)                           | 0.005          | 0.008       | 0.007         | 0.029          |
| Dissolved P (mg/l)                       | 0.004          | 0.005       | 0.005         | 0.007          |
| NO <sub>2</sub> + NO <sub>3</sub> (mg/l) | 0.260          | 0.360       | 0.320         | 0.480          |
| Ammonia (mg/l)                           | 0.030          | 0.032       | 0.030         | 0.040          |

ALL VALUES

|                      |     |     |     |     |
|----------------------|-----|-----|-----|-----|
| Secchi disc (inches) | 110 | 177 | 168 | 252 |
|----------------------|-----|-----|-----|-----|

## B. Biological characteristics:

## 1. Phytoplankton -

| <u>Sampling Date</u> | <u>Dominant Genera</u> | <u>Number per ml</u> |
|----------------------|------------------------|----------------------|
| 05/27/72             | 1. Chroococcus         | 1,663                |
|                      | 2. Fragilaria          | 499                  |
|                      | 3. Dinobryon           | 289                  |
|                      | 4. Synedra             | 181                  |
|                      | 5. Anabaena            | 51                   |
|                      | Other genera           | <u>151</u>           |
|                      | Total                  | 2,834                |
| 07/21/72             | 1. Synedra             | 844                  |
|                      | 2. Dinobryon           | 542                  |
|                      | 3. Fragilaria          | 286                  |
|                      | 4. Navicula            | 75                   |
|                      | 5. Cyclotella          | 45                   |
|                      | Other genera           | <u>160</u>           |
|                      | Total                  | 1,952                |
| 10/14/72             | 1. Scenedesmus         | 1,457                |
|                      | 2. Dinobryon           | 1,080                |
|                      | 3. Flagellates         | 729                  |
|                      | 4. Pediastrum          | 477                  |
|                      | 5. Melosira            | 226                  |
|                      | Other genera           | <u>1,182</u>         |
|                      | Total                  | 5,151                |

2. Chlorophyll a -  
(Because of instrumentation problems during the 1972 sampling, the following values may be in error by plus or minus 20 percent.)

| <u>Sampling Date</u> | <u>Station Number</u> | <u>Chlorophyll a (µg/l)</u> |
|----------------------|-----------------------|-----------------------------|
| 05/27/73             | 01                    | 2.6                         |
|                      | 02                    | 4.1                         |
|                      | 03                    | 3.5                         |
| 07/21/72             | 01                    | 9.0                         |
|                      | 02                    | 5.6                         |
|                      | 03                    | 7.4                         |
| 10/14/72             | 01                    | 1.9                         |
|                      | 02                    | 2.3                         |
|                      | 03                    | 2.6                         |

C. Limiting Nutrient Study:

1. Autoclaved, filtered, and nutrient spiked -

| <u>Spike (mg/l)</u> | <u>Ortho P Conc. (mg/l)</u> | <u>Inorganic N Conc. (mg/l)</u> | <u>Maximum yield (mg/l-dry wt.)</u> |
|---------------------|-----------------------------|---------------------------------|-------------------------------------|
| Control             | 0.001                       | 0.192                           | 0.1                                 |
| 0.010 P             | 0.011                       | 0.192                           | 2.0                                 |
| 0.020 P             | 0.021                       | 0.192                           | 6.3                                 |
| 0.050 P             | 0.051                       | 0.192                           | 8.6                                 |
| 0.050 P + 5.0 N     | 0.051                       | 5.192                           | 14.2                                |
| 0.050 P + 10.0 N    | 0.051                       | 10.192                          | 14.9                                |
| 10.0 N              | 0.001                       | 10.192                          | 0.1                                 |

2. Discussion -

The control yield of the assay alga, Selenastrum capricornutum, indicates that Canandaigua Lake had a relatively low potential for primary production at the time of sampling. The assay also indicates Canandaigua Lake was phosphorus limited at the time of sampling. Note that the addition of phosphorus alone or in combination with nitrogen produced

a yield significantly greater than the control yield, while the addition of only nitrogen did not. The lake data also indicate phosphorus limitation for Canandaigua Lake at all sampling times (N/P ratios were greater than 14/1, and phosphorus limitation would be expected).

#### IV. NUTRIENT LOADINGS (See Appendix C for data)

For the determination of nutrient loadings, the New York National Guard collected monthly near-surface grab samples from each of the tributary sites indicated on the map (page v), except for the high runoff months of April and May when two samples were collected. Sampling was begun in November, 1972, and was completed in October, 1973.

Through an interagency agreement, stream flow estimates for the year of sampling and a "normalized" or average year were provided by the New York District Office of the U.S. Geological Survey for the tributary sites nearest the lake.

In this report, nutrient loads for sampled tributaries were determined by using a modification of a U.S. Geological Survey computer program for calculating stream loadings\*. Nutrient loadings for unsampled "minor tributaries and immediate drainage" ("ZZ" of U.S.G.S.) were estimated by using the means of the nutrient loads, in  $\text{lbs}/\text{mi}^2/\text{year}$ , at stations C-1, D-1, and E-1 and multiplying the means by the ZZ drainage area in  $\text{mi}^2$ . Loadings for Naples Creek were calculated in the same manner. The nutrient loads attributed to the other tributaries are those measured or estimated minus point-source loads, if any.

Bristol Harbor Village, Middlesex, Naples, and Rushville did not participate in the Survey, and nutrient loads for these sources were estimated\*.

\* See Working Paper No. 1.

## A. Waste Sources:

## 1. Known municipal -

| <u>Name</u>                           | <u>Pop.<br/>Served *</u> | <u>Treatment</u>                  | <u>Mean<br/>Flow (mgd)</u> | <u>Receiving<br/>Water</u> |
|---------------------------------------|--------------------------|-----------------------------------|----------------------------|----------------------------|
| Middlesex<br>Valley Central<br>School | 640                      | septic tanks<br>& sand filters    | ?                          | West River                 |
| Rushville<br>Village                  | 568                      | storm sewers<br>& private systems | ?                          | West River                 |
| Naples                                | 1,240                    | primary                           | ?                          | Naples Creek               |
| Bristol Harbor<br>Village             | 250                      | secondary                         | ?                          | Seneca Point<br>Gulley     |

## 2. Known industrial - None

---

\* Carcich, 1974.

## B. Annual Total Phosphorus Loading - Average Year:

## 1. Inputs -

| <u>Source</u>                                                   | <u>lbs P/<br/>yr</u> | <u>% of<br/>total</u> |
|-----------------------------------------------------------------|----------------------|-----------------------|
| a. Tributaries (non-point load) -                               |                      |                       |
| West River                                                      | 1,050                | 7.9                   |
| Seneca Point Gulley                                             | 70                   | 0.5                   |
| Unnamed Stream (C-1)                                            | 320                  | 2.4                   |
| Barnes Gulley                                                   | 20                   | 0.2                   |
| Menteth Gulley                                                  | 60                   | 0.4                   |
| Naples Creek                                                    | 1,570                | 11.8                  |
| b. Minor tributaries & immediate<br>drainage (non-point load) - | 2,440                | 18.3                  |
| c. Known municipal STP's -                                      |                      |                       |
| Bristol Harbor Village                                          | 630                  | 4.7                   |
| Middlesex                                                       | 1,600                | 12.0                  |
| Naples                                                          | 3,100                | 23.3                  |
| Rushville                                                       | 140                  | 1.0                   |
| d. Septic tanks* -                                              | 660                  | 5.0                   |
| e. Known industrial - None                                      | -                    | -                     |
| f. Direct precipitation** -                                     | <u>1,660</u>         | <u>12.5</u>           |
| Total                                                           | 13,320               | 100.0                 |

## 2. Outputs -

Feeder Canal & outlet 4,630

## 3. Net annual P accumulation - 8,690 pounds

\* Based on 1,052 lakeshore residences; see Working Paper No. 1.

\*\* See Working Paper No. 1.

## C. Annual Total Nitrogen Loading - Average Year:

## 1. Inputs -

| <u>Source</u>                                                   | <u>lbs N/<br/>yr</u> | <u>% of<br/>total</u> |
|-----------------------------------------------------------------|----------------------|-----------------------|
| a. Tributaries (non-point load) -                               |                      |                       |
| West River                                                      | 51,660               | 14.8                  |
| Seneca Point Gulley                                             | 4,140                | 1.2                   |
| Unnamed Stream (C-1)                                            | 7,170                | 2.1                   |
| Barnes Gulley                                                   | 1,180                | 0.3                   |
| Menteth Gulley                                                  | 6,100                | 1.7                   |
| Naples Creek                                                    | 57,380               | 16.4                  |
| b. Minor tributaries & immediate<br>drainage (non-point load) - | 89,020               | 25.4                  |
| c. Known municipal STP's -                                      |                      |                       |
| Bristol Harbor Village                                          | 1,880                | 0.5                   |
| Middlesex                                                       | 4,800                | 1.4                   |
| Naples                                                          | 9,300                | 2.7                   |
| Rushville                                                       | 5,340                | 1.5                   |
| d. Septic tanks* -                                              | 9,890                | 2.8                   |
| e. Known industrial - None                                      | -                    | -                     |
| f. Direct precipitation** -                                     | <u>102,350</u>       | <u>29.2</u>           |
| Total                                                           | 350,210              | 100.0                 |

## 2. Outputs -

Lake outlet - Feeder Canal &  
outlet 174,560

## 3. Net annual N accumulation - 175,650 pounds

\* Based on 1,052 lakeshore residences; see Working Paper No. 1.

\*\* See Working Paper No. 1.

## D. Mean Annual Non-point Nutrient Export by Subdrainage Area:

| <u>Tributary</u>     | <u>lbs P/mi<sup>2</sup>/yr</u> | <u>lbs N/mi<sup>2</sup>/yr</u> |
|----------------------|--------------------------------|--------------------------------|
| West River           | 36                             | 1,763                          |
| Seneca Point Gulley  | 16                             | 941                            |
| Unnamed Stream (C-1) | 68                             | 1,523                          |
| Barnes Gulley        | 15                             | 908                            |
| Menteth Gulley       | 10                             | 1,017                          |

## E. Yearly Loading Rates:

In the following table, the existing phosphorus loading rates are compared to those proposed by Vollenweider (in press). Essentially, his "dangerous" rate is the rate at which the receiving waters would become eutrophic or remain eutrophic; his "permissible" rate is that which would result in the receiving water remaining oligotrophic or becoming oligotrophic if morphometry permitted. A mesotrophic rate would be considered one between "dangerous" and "permissible".

| <u>Units</u>             | <u>Total Phosphorus</u> |                    | <u>Total Nitrogen</u> |                    |
|--------------------------|-------------------------|--------------------|-----------------------|--------------------|
|                          | <u>Total</u>            | <u>Accumulated</u> | <u>Total</u>          | <u>Accumulated</u> |
| lbs/acre/yr              | 1.3                     | 0.8                | 33.0                  | 16.5               |
| grams/m <sup>2</sup> /yr | 0.14                    | 0.09               | 3.7                   | 1.9                |

Vollenweider loading rates for phosphorus  
(g/m<sup>2</sup>/yr) based on mean depth and mean  
hydraulic retention time of Canandaigua Lake:

|                                   |      |
|-----------------------------------|------|
| "Dangerous" (eutrophic rate)      | 0.32 |
| "Permissible" (oligotrophic rate) | 0.16 |

## V. LITERATURE REVIEWED

- Anonymous, 1972. Canandaigua Lake study. Part I: Coliform, phosphate, nitrate. Bulletin 2, Delta Laboratories, Inc.
- Anonymous, 1973. Canandaigua Lake study. Part II: Temperature, pH, dissolved oxygen, dissolved solids. Bulletin 5, Delta Laboratories, Inc.
- Birge, Edward A., and Chancey Juday, 1914. A limnological study of the Finger Lakes of New York. Bull. U.S. Bureau Fisheries, 32: 525-614.
- Carcich, Italo, 1974. Personal communication (wastewater treatment plant at Bristol Harbor Village; populations served). NY State Dept. Environmental Conservation.
- Fitze, Fred, 1972. A winter study of Canandaigua Lake. MS, Eisenhower Coll., Seneca Falls.
- Forest, Herman S., William C. Grow, and Tracy Maxwell, 1971. Some sources of input to Canandaigua Lake and their contribution to the quality of the environment-1971. MS, Envir. Res. Center, State Univ. Coll., Geneseo.
- Gelser, Bruce M., 1974. Personal communication (lake morphometry). Rochester.
- Grow, William C., 1970. A water quality survey of West River, Naples Creek, and Canandaigua Lake, summer and fall, 1970. MS, State Univ. Coll., Geneseo.
- Vollenweider, Richard A., (in press). Input-output models. Schweiz. A. Hydrol.
- Winship, Timothy R., and Sheila Colf, 1971. A study of the western tributaries and outlet of Canandaigua Lake. MS.
- Winship, Timothy R., Anthony Ellman, and Sheila Colf, 1973. Report of the assistant watershed inspector for Canandaigua Lake, summer, 1973. MS.

VII. APPENDICES

APPENDIX A

TRIBUTARY FLOW DATA

11/26/74

## TRIBUTARY FLOW INFORMATION FOR NEW YORK

LAKE CODE 3604 CANANDAIGUA LAKE

TOTAL DRAINAGE AREA OF LAKE 194.00

| TRIBUTARY | SUB-DRAINAGE AREA | JAN   | FEB   | MAR    | APR    | MAY    | JUN   | JUL   | AUG   | SEP   | OCT   | NOV   | DEC   | MEAN  |
|-----------|-------------------|-------|-------|--------|--------|--------|-------|-------|-------|-------|-------|-------|-------|-------|
| 3604A1    | 29.30             | 11.00 | 21.00 | 62.00  | 54.00  | 26.00  | 8.50  | 0.70  | 0.40  | 0.30  | 1.80  | 5.20  | 14.00 | 17.13 |
| 3604B1    | 4.41              | 1.70  | 3.20  | 9.00   | 7.90   | 3.90   | 1.40  | 0.30  | 0.20  | 0.07  | 0.50  | 0.80  | 2.30  | 2.60  |
| 3604C1    | 4.35              | 1.83  | 3.30  | 9.30   | 8.20   | 4.00   | 1.40  | 0.30  | 0.20  | 0.07  | 0.50  | 0.80  | 2.40  | 2.68  |
| 3604D1    | 1.28              | 0.50  | 0.80  | 2.40   | 2.10   | 1.00   | 0.40  | 0.08  | 0.06  | 0.02  | 0.10  | 0.20  | 0.60  | 0.69  |
| 3604E1    | 6.03              | 2.40  | 4.40  | 12.00  | 11.00  | 5.40   | 1.90  | 0.40  | 0.30  | 0.09  | 0.60  | 1.10  | 3.10  | 3.55  |
| 3604F1    | 184.00            | 54.00 | 65.00 | 140.00 | 190.00 | 130.00 | 69.00 | 35.00 | 35.00 | 35.00 | 35.00 | 35.00 | 45.00 | 72.28 |
| 3604G1    | 184.00            | 54.00 | 65.00 | 140.00 | 190.00 | 130.00 | 69.00 | 37.00 | 10.00 | 5.00  | 13.00 | 20.00 | 44.00 | 64.68 |
| 3604H1    | 47.70             | 33.00 | 60.00 | 170.00 | 150.00 | 74.00  | 26.00 | 5.50  | 4.20  | 1.30  | 8.60  | 15.00 | 43.00 | 49.14 |
| 3604Z1    | 90.63             | 35.00 | 65.00 | 180.00 | 160.00 | 79.00  | 27.00 | 5.90  | 4.50  | 1.40  | 9.20  | 15.00 | 46.00 | 52.25 |

## SUMMARY

TOTAL DRAINAGE AREA OF LAKE = 184.00  
 SUM OF SUB-DRAINAGE AREAS = 184.00  
 TOTAL FLOW IN = 1538.99  
 TOTAL FLOW OUT = 1645.00

## MEAN MONTHLY FLOWS AND DAILY FLOWS

| TRIBUTARY | MONTH | YEAR | MEAN FLOW | DAY | FLOW   | DAY   | FLOW |
|-----------|-------|------|-----------|-----|--------|-------|------|
| 3604A1    | 11    | 72   | 64.00     | 5   | 28.00  |       |      |
|           | 12    | 72   | 94.00     | 2   | 50.00  |       |      |
|           | 1     | 73   | 32.00     | 6   | 42.00  |       |      |
|           | 2     | 73   | 36.00     | 4   | 130.00 |       |      |
|           | 3     | 73   | 80.00     | 4   | 220.00 |       |      |
|           | 4     | 73   | 51.00     | 21  | 150.00 | 18.00 |      |
|           | 5     | 73   | 30.00     | 19  | 33.00  | 15.00 |      |
|           | 6     | 73   | 26.00     | 3   | 15.00  |       |      |
|           | 7     | 73   | 1.40      | 28  | 0.60   |       |      |
|           | 8     | 73   | 0.30      | 17  | 0.50   |       |      |
| 3604B1    | 9     | 73   | 0.20      | 9   | 0.30   |       |      |
|           | 10    | 73   | 2.40      | 6   | 0.20   |       |      |
|           | 11    | 72   | 6.00      | 5   | 4.50   |       |      |
|           | 12    | 72   | 2.50      | 2   | 3.80   |       |      |
|           | 1     | 73   | 5.50      | 6   | 2.50   |       |      |
|           | 2     | 73   | 12.00     | 4   | 18.00  |       |      |
|           | 3     | 73   | 11.00     | 7   | 33.00  |       |      |
|           | 4     | 73   | 4.70      | 21  | 23.00  | 2.80  |      |
|           | 5     | 73   | 4.30      | 19  | 5.10   | 2.50  |      |
|           | 6     | 73   | 0.40      | 3   | 2.40   |       |      |
| 3604C1    | 7     | 73   | 0.20      | 28  | 0.30   |       |      |
|           | 8     | 73   | 0.20      | 17  | 0.20   |       |      |
|           | 9     | 73   | 0.20      | 9   | 0.20   |       |      |
|           | 10    | 73   | 0.20      | 6   | 0.20   |       |      |

11/26/74

## TRIBUTARY FLOW INFORMATION FOR NEW YORK

LAKE CODE 3604 CANANDAIGUA LAKE

## MEAN MONTHLY FLOWS AND DAILY FLOWS

| TRIBUTARY | MONTH | YEAR | MEAN FLOW | DAY | FLOW   | DAY | FLOW   |
|-----------|-------|------|-----------|-----|--------|-----|--------|
| 3604C1    | 11    | 72   | 2.40      | 5   | 4.50   |     |        |
|           | 12    | 72   | 8.40      | 2   | 3.40   |     |        |
|           | 1     | 73   | 2.70      | 6   | 2.70   |     |        |
|           | 2     | 73   | 5.70      | 4   | 19.00  |     |        |
|           | 3     | 73   | 12.00     | 4   | 34.00  |     |        |
|           | 4     | 73   | 11.00     | 7   | 24.00  | 21  | 2.90   |
|           | 5     | 73   | 4.80      | 5   | 5.30   | 19  | 2.50   |
|           | 6     | 73   | 4.30      | 3   | 2.50   |     |        |
|           | 7     | 73   | 0.40      | 28  | 0.30   |     |        |
|           | 8     | 73   | 0.20      | 17  | 0.20   |     |        |
| 3604D1    | 9     | 73   | 0.20      | 9   | 0.20   |     |        |
|           | 10    | 73   | 0.20      | 6   | 0.20   |     |        |
|           | 11    | 72   | 0.60      | 5   | 1.00   |     |        |
|           | 12    | 72   | 2.10      | 2   | 1.00   |     |        |
|           | 1     | 73   | 0.70      | 6   | 0.60   |     |        |
|           | 2     | 73   | 1.40      | 4   | 4.90   |     |        |
|           | 3     | 73   | 3.20      | 4   | 8.50   |     |        |
|           | 4     | 73   | 2.80      | 7   | 6.10   | 21  | 0.70   |
|           | 5     | 73   | 1.20      | 5   | 1.30   | 19  | 0.60   |
|           | 6     | 73   | 1.70      | 3   | 0.70   |     |        |
| 3604E1    | 7     | 73   | 0.10      | 28  | 0.10   |     |        |
|           | 8     | 73   | 0.10      | 17  | 0.10   |     |        |
|           | 9     | 73   | 0.10      | 9   | 0.10   |     |        |
|           | 10    | 73   | 0.10      | 6   | 0.10   |     |        |
|           | 11    | 72   | 3.30      | 5   | 5.80   |     |        |
|           | 12    | 72   | 11.00     | 2   | 5.20   |     |        |
|           | 1     | 73   | 4.00      | 6   | 3.50   |     |        |
|           | 2     | 73   | 7.60      | 4   | 25.00  |     |        |
|           | 3     | 73   | 16.00     | 4   | 44.00  |     |        |
|           | 4     | 73   | 15.00     | 7   | 31.00  | 21  | 3.90   |
| 3604F1    | 5     | 73   | 6.50      | 5   | 7.10   | 19  | 3.90   |
|           | 6     | 73   | 5.80      | 3   | 3.40   |     |        |
|           | 7     | 73   | 0.60      | 28  | 0.40   |     |        |
|           | 8     | 73   | 0.30      | 17  | 0.40   |     |        |
|           | 9     | 73   | 0.20      | 9   | 0.30   |     |        |
|           | 10    | 73   | 0.20      | 6   | 0.20   |     |        |
|           | 11    | 72   | 130.00    | 5   | 35.00  |     |        |
|           | 12    | 72   | 250.00    | 2   | 210.00 |     |        |
|           | 1     | 73   | 180.00    | 6   | 250.00 |     |        |
|           | 2     | 73   | 110.00    | 4   | 270.00 |     |        |
|           | 3     | 73   | 180.00    | 4   | 200.00 |     |        |
|           | 4     | 73   | 260.00    | 7   | 300.00 | 21  | 240.00 |
|           | 5     | 73   | 110.00    | 5   | 50.00  | 19  | 190.00 |
|           | 6     | 73   | 110.00    | 3   | 150.00 |     |        |
|           | 7     | 73   | 23.00     | 28  | 30.00  |     |        |
|           | 8     | 73   | 36.00     | 17  | 27.00  |     |        |
|           | 9     | 73   | 35.00     | 9   | 35.00  |     |        |
|           | 10    | 73   | 35.00     | 6   | 35.00  |     |        |

11/26/74

## TRIBUTARY FLOW INFORMATION FOR NEW YORK

LAKE CODE 3604 CANANDAIGUA LAKE

## MEAN MONTHLY FLOWS AND DAILY FLOWS

| TRIBUTARY | MONTH | YEAR | MEAN FLOW | DAY | FLOW   | DAY | FLOW   |
|-----------|-------|------|-----------|-----|--------|-----|--------|
| 360461    | 11    | 72   | 130.00    | 5   | 33.00  |     |        |
|           | 12    | 72   | 250.00    | 2   | 210.00 |     |        |
|           | 1     | 73   | 125.00    | 6   | 250.00 |     |        |
|           | 2     | 73   | 110.00    | 4   | 270.00 |     |        |
|           | 3     | 73   | 140.00    | 4   | 200.00 |     |        |
|           | 4     | 73   | 260.00    | 7   | 300.00 | 21  | 240.00 |
|           | 5     | 73   | 120.00    | 5   | 54.00  | 19  | 200.00 |
|           | 6     | 73   | 110.00    | 3   | 160.00 |     |        |
|           | 7     | 73   | 0.0       | 24  | 0.0    |     |        |
|           | 8     | 73   | 0.0       | 17  | 0.0    |     |        |
|           | 9     | 73   | 12.00     | 9   | 24.00  |     |        |
|           | 10    | 73   | 11.00     | 6   | 2.00   |     |        |
|           | 11    | 72   | 45.00     | 5   | 41.00  |     |        |
|           | 12    | 72   | 150.00    | 2   | 74.00  |     |        |
|           | 1     | 73   | 49.00     | 6   | 50.00  |     |        |
|           | 2     | 73   | 100.00    | 4   | 350.00 |     |        |
|           | 3     | 73   | 220.00    | 4   | 520.00 |     |        |
|           | 4     | 73   | 200.00    | 7   | 430.00 | 21  | 53.00  |
|           | 5     | 73   | 89.00     | 5   | 97.00  | 19  | 47.00  |
|           | 6     | 73   | 70.00     | 3   | 42.00  |     |        |
| 360472    | 7     | 73   | 7.60      | 24  | 5.10   |     |        |
|           | 8     | 73   | 3.50      | 17  | 5.00   |     |        |
|           | 9     | 73   | 2.80      | 9   | 4.00   |     |        |
|           | 10    | 73   | 3.50      | 4   | 3.10   |     |        |
|           | 11    | 72   | 45.00     |     |        |     |        |
|           | 12    | 72   | 170.00    |     |        |     |        |
|           | 1     | 73   | 53.00     |     |        |     |        |
|           | 2     | 73   | 110.00    |     |        |     |        |
|           | 3     | 73   | 240.00    |     |        |     |        |
|           | 4     | 73   | 220.00    |     |        |     |        |
|           | 5     | 73   | 95.00     |     |        |     |        |
|           | 6     | 73   | 43.00     |     |        |     |        |
|           | 7     | 73   | 4.10      |     |        |     |        |
|           | 8     | 73   | 3.80      |     |        |     |        |
|           | 9     | 73   | 3.10      |     |        |     |        |
|           | 10    | 73   | 3.70      |     |        |     |        |

APPENDIX B

PHYSICAL and CHEMICAL DATA

STORET RETRIEVAL DATE 74/11/26

360401  
42 51 44.0 077 16 05.0  
CANANDAIGUA LAKE  
36 NEW YORK

| DATE FROM TO |  | TIME DEPTH OF DAY |  | 00010 WATER TEMP CENT |  | 00300 DO MG/L |  | 00077 TRANSP SECCHI INCHES |  | 00094 CONDUCTIVITY FIELD MICROMHO |  | 00400 PH SU |  | 00410 T ALK CAC03 MG/L |  | 00630 NO2&NO3 N-TOTAL MG/L |  | 00610 NH3-N TOTAL MG/L |  | 00665 PHOS-TOT MG/L P |  | 00666 PHOS-DIS MG/L P |  |
|--------------|--|-------------------|--|-----------------------|--|---------------|--|----------------------------|--|-----------------------------------|--|-------------|--|------------------------|--|----------------------------|--|------------------------|--|-----------------------|--|-----------------------|--|
| 72/05/27     |  | 17 00 0000        |  | 14.9                  |  | 12.4          |  | 156                        |  | 280                               |  | 8.30        |  | 115                    |  | 0.340                      |  | 0.020                  |  | 0.005                 |  | 0.005                 |  |
|              |  | 17 00 0011        |  | 12.9                  |  | 13.2          |  |                            |  | 300                               |  | 8.20        |  | 114                    |  | 0.320                      |  | 0.010                  |  | 0.006                 |  | 0.002                 |  |
| 72/07/21     |  | 11 20 0000        |  |                       |  |               |  | 128                        |  | 300                               |  | 8.30        |  | 110                    |  | 0.290                      |  | 0.070                  |  | 0.012                 |  | 0.008                 |  |
|              |  | 11 20 0004        |  | 26.1                  |  | 8.1           |  |                            |  | 432                               |  | 8.00        |  | 109                    |  | 0.270                      |  | 0.040                  |  | 0.011                 |  | 0.007                 |  |
|              |  | 11 20 0015        |  | 25.8                  |  | 9.0           |  |                            |  | 429                               |  | 7.90        |  | 109                    |  | 0.270                      |  | 0.050                  |  | 0.012                 |  | 0.006                 |  |
| 72/10/14     |  | 10 50 0000        |  |                       |  |               |  | 180                        |  | 320                               |  | 8.20        |  | 111                    |  | 0.260                      |  | 0.040                  |  | 0.007                 |  | 0.005                 |  |
|              |  | 10 50 0004        |  | 12.6                  |  | 9.8           |  |                            |  | 310                               |  | 8.20        |  | 108                    |  | 0.260                      |  | 0.040                  |  | 0.007                 |  | 0.004                 |  |
|              |  | 10 50 0011        |  | 12.5                  |  | 10.0          |  |                            |  | 310                               |  | 8.20        |  | 108                    |  | 0.260                      |  | 0.040                  |  | 0.007                 |  | 0.004                 |  |

| DATE FROM TO |            | TIME OF DAY |      | DEPTH FEET |      | 32217 CHLOROPHYL A UG/L |  |
|--------------|------------|-------------|------|------------|------|-------------------------|--|
| 72/05/27     | 17 00 0000 | 17 00 0000  | 2.6J | 9.0J       | 1.9J |                         |  |
|              |            |             |      |            |      |                         |  |
| 72/07/21     | 11 20 0000 | 11 20 0000  |      |            |      |                         |  |
|              |            |             |      |            |      |                         |  |
| 72/10/14     | 10 50 0000 | 10 50 0000  |      |            |      |                         |  |
|              |            |             |      |            |      |                         |  |

J VALUE KNOWN TO BE IN ERROR

STORET RETRIEVAL DATE 74/11/26

360402  
42 47 48.0 077 17 12.0  
CANANDAIGUA LAKE  
36 NEW YORK

|                    |                         | 11EPALES                       |                     | 2111202                             |                                            | DEPTH             |                                |                                     |                                 |                           |                           |
|--------------------|-------------------------|--------------------------------|---------------------|-------------------------------------|--------------------------------------------|-------------------|--------------------------------|-------------------------------------|---------------------------------|---------------------------|---------------------------|
|                    |                         | 3                              |                     | 0219 FEET                           |                                            |                   |                                |                                     |                                 |                           |                           |
| DATE<br>FROM<br>TO | TIME DEPTH<br>OF<br>DAY | 00010<br>WATER<br>TEMP<br>CENT | 00300<br>DO<br>MG/L | 00077<br>TRANSP<br>SECCHI<br>INCHES | 00094<br>CONDUCTIVITY<br>FIELD<br>MICROMHO | 00400<br>PH<br>SU | 00410<br>TALK<br>CACO3<br>MG/L | 00630<br>NO2&NO3<br>N-TOTAL<br>MG/L | 00610<br>NH3-N<br>TOTAL<br>MG/L | 00665<br>PHOS-TOT<br>MG/L | 00666<br>PHOS-DIS<br>MG/L |
|                    |                         |                                |                     |                                     |                                            |                   |                                |                                     |                                 |                           |                           |
| 72/05/27           | 17 30 0000              | 12.7                           | 12.4                | 144                                 | 300                                        | 6.30              | 115                            | 0.310                               | 0.020                           | 0.008                     | 0.002                     |
|                    | 17 30 0010              | 10.7                           | 12.8                |                                     | 300                                        | 8.20              | 114                            | 0.350                               | 0.050                           | 0.010                     | 0.009                     |
|                    | 17 30 0030              | 8.3                            | 13.4                |                                     | 300                                        | 8.20              | 118                            | 0.360                               | 0.020                           | 0.009                     | 0.010                     |
| 72/07/21           | 11 52 0000              |                                |                     | 110                                 | 300                                        | 7.80              | 112                            | 0.310                               | 0.060                           | 0.015                     | 0.010                     |
|                    | 11 52 0004              | 23.3                           | 8.6                 |                                     | 384                                        | 8.00              | 111                            | 0.310                               | 0.040                           | 0.017                     | 0.008                     |
|                    | 11 52 0015              | 19.9                           | 8.2                 |                                     | 340                                        | 7.90              | 111                            | 0.340                               | 0.070                           | 0.028                     | 0.009                     |
|                    | 11 52 0130              | 4.4                            | 11.0                |                                     | 283                                        | 7.30              | 116                            | 0.420                               | 0.090                           | 0.037                     | 0.010                     |
|                    | 11 52 0219              | 4.6                            | 10.1                |                                     | 298                                        | 7.20              | 116                            | 0.450                               | 0.090                           | 0.037                     | 0.010                     |
|                    | 72/10/14                | 11 10 0000                     |                     | 252                                 | 320                                        | 8.15              | 104                            | 0.290                               | 0.030                           | 0.007                     | 0.005                     |
|                    | 11 10 0004              | 13.8                           | 9.8                 |                                     | 318                                        | 8.15              | 104                            | 0.290                               | 0.030                           | 0.008                     | 0.004                     |
|                    | 11 10 0015              | 13.8                           | 9.6                 |                                     | 318                                        | 8.15              | 103                            | 0.290                               | 0.030                           | 0.007                     | 0.004                     |
|                    | 11 10 0030              | 13.8                           | 9.4                 |                                     | 320                                        | 8.15              | 105                            | 0.290                               | 0.030                           | 0.006                     | 0.005                     |
|                    | 11 10 0050              | 13.1                           | 9.4                 |                                     | 318                                        | 8.10              | 83                             | 0.370                               | 0.030                           | 0.006                     | 0.004                     |
|                    | 11 10 0075              | 10.4                           | 9.4                 |                                     | 320                                        | 7.90              | 83                             | 0.390                               | 0.030                           | 0.005                     | 0.004                     |
|                    | 11 10 0100              | 5.7                            | 9.6                 |                                     | 325                                        | 7.75              | 115                            | 0.440                               | 0.030                           | 0.005                     | 0.004                     |
|                    | 11 10 0140              | 4.8                            | 9.0                 |                                     | 335                                        | 7.70              | 120                            | 0.460                               | 0.030                           | 0.008                     | 0.005                     |
|                    | 11 10 0180              | 4.6                            | 8.8                 |                                     | 330                                        | 7.65              | 117                            | 0.470                               | 0.030                           | 0.009                     | 0.006                     |
|                    | 11 10 0218              | 4.5                            | 8.0                 |                                     | 340                                        | 7.65              | 117                            | 0.480                               | 0.040                           | 0.029                     | 0.007                     |

21

| DATE<br>FROM<br>TO | TIME<br>OF<br>DAY | DEPTH<br>FEET | CHLOROPHYL<br>A<br>UG/L |  |
|--------------------|-------------------|---------------|-------------------------|--|
|                    |                   |               |                         |  |
| 72/05/27           | 17 30 0000        | 4.1J          |                         |  |
| 72/07/21           | 11 52 0000        | 5.6J          |                         |  |
| 72/10/14           | 11 10 0000        | 2.3J          |                         |  |

J VALUE KNOWN TO BE IN ERROR

360403  
42 42 00.0 077 21 02.0  
CANANDAIGUA LAKE  
36 NEW YORK

| STATION  | DATE | TIME | DEPTH     | TEMP. | SURFACE WIND | DIRECTION | WAVE HEIGHT | SEA STATE | CLOUDS | REMARKS |
|----------|------|------|-----------|-------|--------------|-----------|-------------|-----------|--------|---------|
| 11EPALES |      |      | 211120Z   |       |              |           |             |           |        |         |
|          |      |      | 0000 FEET |       |              |           |             |           |        |         |

| DATE<br>FROM<br>TO | TIME<br>OF<br>DAY | DEPTH<br>FEET | 00010<br>WATER<br>TEMP<br>CENT | 00300<br>DO<br>MG/L | 00077<br>TRANSP<br>SECCHI<br>INCHES | 00094<br>CNDUCTVY<br>FIELD<br>MICROMHO | 00400<br>PH<br>SU | 00410<br>T ALK<br>CACO3<br>MG/L | 00630<br>NO2&NO3<br>N-TOTAL<br>MG/L | 00610<br>NH3-N<br>TOTAL<br>MG/L | 00665<br>PHOS-TOT<br>MG/L | 00666<br>PHOS-DIS<br>MG/L |
|--------------------|-------------------|---------------|--------------------------------|---------------------|-------------------------------------|----------------------------------------|-------------------|---------------------------------|-------------------------------------|---------------------------------|---------------------------|---------------------------|
| 72/05/27           | 18 00             | 0000          | 10.1                           | 14.9                | 216                                 | 275                                    | 8.20              | 116                             | 0.370                               | 0.040                           | 0.011                     | 0.006                     |
|                    | 18 00             | 0010          | 5.9                            | 16.5                |                                     | 278                                    | 8.10              | 115                             | 0.380                               | 0.030                           | 0.012                     | 0.008                     |
|                    | 18 00             | 0030          | 5.1                            | 17.9                |                                     | 275                                    | 8.00              | 114                             | 0.410                               | 0.050                           | 0.012                     | 0.008                     |
| 72/07/21           | 18 00             | 0000          |                                |                     |                                     | 300                                    | 8.10              | 111                             | 0.330                               | 0.060                           | 0.016                     | 0.010                     |
|                    | 12 44             | 0004          | 22.1                           | 8.6                 |                                     | 392                                    | 8.00              | 111                             | 0.320                               | 0.050                           | 0.027                     | 0.013                     |
|                    | 12 44             | 0015          | 19.9                           | 8.0                 |                                     | 366                                    | 7.80              | 111                             | 0.330                               | 0.110                           | 0.096                     | 0.013                     |
| 72/10/14           | 12 44             | 0080          |                                |                     |                                     | 265                                    |                   |                                 |                                     | 0.080                           | 0.015                     | 0.009                     |
|                    | 12 44             | 0086          | 6.1                            | 11.6                |                                     | 310                                    | 7.30              | 114                             | 0.400                               | 0.080                           | 0.025                     | 0.008                     |
|                    | 12 44             | 0125          | 4.6                            | 9.8                 | 228                                 | 273                                    | 7.30              | 115                             | 0.430                               | 0.080                           | 0.007                     | 0.007                     |
| 72/10/14           | 12 00             | 0000          |                                |                     |                                     | 310                                    | 8.10              | 106                             | 0.310                               | 0.030                           | 0.009                     | 0.005                     |
|                    | 12 00             | 0004          | 13.3                           | 9.8                 |                                     | 308                                    | 8.10              | 106                             | 0.310                               | 0.030                           | 0.007                     | 0.005                     |
|                    | 12 00             | 0015          | 13.3                           | 9.6                 |                                     | 308                                    | 8.10              | 109                             | 0.320                               | 0.030                           | 0.007                     | 0.006                     |
| 72/10/14           | 12 00             | 0030          | 13.2                           | 9.6                 |                                     | 304                                    | 8.10              | 104                             | 0.320                               | 0.030                           | 0.009                     | 0.006                     |
|                    | 12 00             | 0050          | 13.2                           | 9.6                 |                                     | 304                                    | 8.05              | 106                             | 0.320                               | 0.030                           | 0.007                     | 0.005                     |
|                    | 12 00             | 0070          | 7.6                            | 9.6                 |                                     | 320                                    | 7.75              | 107                             | 0.420                               | 0.030                           | 0.006                     | 0.004                     |
| 72/10/14           | 12 00             | 0090          | 5.9                            | 8.6                 |                                     | 320                                    | 7.70              | 113                             | 0.440                               | 0.040                           | 0.008                     | 0.005                     |
|                    | 12 00             | 0100          | 4.9                            | 8.6                 |                                     | 330                                    | 7.60              | 112                             | 0.470                               | 0.040                           | 0.008                     | 0.005                     |
|                    | 12 00             | 0120          |                                |                     |                                     | 330                                    | 7.60              | 109                             | 0.470                               | 0.030                           | 0.009                     | 0.005                     |

| DATE<br>FROM<br>TO | TIME<br>OF<br>DAY | DEPTH<br>FEET | CHLOROPHYL<br>A<br>UG/L |
|--------------------|-------------------|---------------|-------------------------|
| 77/05/27           | 18 00             | 0000          | 3.5J                    |
| 77/07/21           | 12 44             | 0000          | 7.4J                    |
| 77/10/14           | 12 00             | 0000          | 2.6J                    |

J VALUE KNOWN TO BE IN ERROR

APPENDIX C

TRIBUTARY DATA

STORET RETRIEVAL DATE 74/11/26

3604A1 LS3604A1  
42 41 00.0 077 14 00.0  
WEST RIVER  
34 7.5 MIDDLESEA  
1/CANANDAIGUA LAKE  
LGT DUTY RD IN MIDDLE SEX BELO STP  
11EPALES 2111204  
0000 FEET DEPTH

| DATE<br>FROM<br>TO | TIME<br>OF<br>DAY | DEPTH<br>FEET | 00630<br>NO <sub>3</sub> -N<br>TOTAL<br>MG/L | 00625<br>TOT KJEL<br>N<br>MG/L | 00610<br>NH <sub>3</sub> -N<br>TOTAL<br>MG/L | 00671<br>PHOS-DIS<br>ORTHO<br>MG/L P | 00665<br>PHOS-TOT<br>MG/L P |
|--------------------|-------------------|---------------|----------------------------------------------|--------------------------------|----------------------------------------------|--------------------------------------|-----------------------------|
| 72/11/05           | 14                | 20            | 0.870                                        | 0.600                          | 0.078                                        | 0.046                                | 0.069                       |
| 72/12/02           | 13                | 50            | 2.250                                        | 0.340                          | 0.021                                        | 0.021                                | 0.033                       |
| 73/01/06           | 14                | 10            | 2.000                                        | 0.056                          | 0.035                                        | 0.020                                | 0.056                       |
| 73/02/04           | 12                | 40            | 2.500                                        | 0.420                          | 0.039                                        | 0.023                                | 0.055                       |
| 73/03/04           | 08                | 59            | 2.600                                        | 1.230                          | 0.097                                        | 0.032                                | 0.200                       |
| 73/04/07           | 11                | 15            | 2.400                                        | 0.580                          | 0.066                                        | 0.054                                | 0.080                       |
| 73/04/21           | 10                | 10            | 0.200                                        | 0.700                          | 0.042                                        | 0.046                                | 0.105                       |
| 73/05/05           | 12                | 40            | 1.020                                        | 1.540                          | 0.035                                        | 0.044                                | 0.070                       |
| 73/05/19           | 05                | 35            | 0.320                                        | 0.520                          | 0.022                                        | 0.066                                | 0.115                       |
| 73/06/03           | 13                | 00            | 0.520                                        | 1.150                          | 0.078                                        | 0.105                                | 0.155                       |
| 73/07/28           | 14                | 35            | 0.010K                                       | 1.470                          | 0.036                                        | 0.028                                | 0.095                       |
| 73/08/17           | 18                | 25            | 0.010K                                       | 0.630                          | 0.018                                        | 0.027                                | 0.090                       |
| 73/09/09           | 09                | 15            | 0.010K                                       | 1.150                          | 0.063                                        | 0.021                                | 0.105                       |
| 73/10/04           | 14                | 00            | 0.021                                        | 0.320                          | 0.020                                        | 0.005K                               | 0.055                       |

K VALUE KNOWN TO 45  
LESS THAN INDICATED

STRET RETRIEVAL DATE 74/11/26

3404A2 LS3604A2  
42 43 00.0 077 16 00.0  
WEST RIVER  
36 7.5 MIDDLESEX  
1/CANANDAIGUA LAKE  
ST HWY 245 RDG HELD RUSHVILLE STP  
11EPALES 2111204  
4 C000 FEET DEPTH

| DATE<br>FROM<br>TO | TIME<br>OF<br>DAY | DEPTH<br>FEET | 00630<br>NO2&NO3<br>N-TOTAL<br>MG/L | 00625<br>TUT KJEL<br>N<br>MG/L | 00610<br>NH3-N<br>TOTAL<br>MG/L | 00671<br>PHOS-01S<br>URTHO<br>MG/L P | 00665<br>PHOS-TOT<br>MG/L P |
|--------------------|-------------------|---------------|-------------------------------------|--------------------------------|---------------------------------|--------------------------------------|-----------------------------|
| 72/11/05           | 14 50             |               | 0.975                               | 0.550                          | 0.087                           | 0.048                                | 0.060                       |
| 72/12/02           | 13 40             |               | 2.800                               | 0.340                          | 0.009                           | 0.024                                | 0.033                       |
| 73/02/04           | 12 20             |               | 3.200                               | 0.240                          | 0.026                           | 0.024                                | 0.055                       |
| 73/03/04           | 08 40             |               | 3.200                               | 1.540                          | 0.092                           | 0.044                                | 0.260                       |
| 73/04/07           | 10 40             |               | 3.100                               | 0.750                          | 0.140                           | 0.084                                | 0.120                       |
| 73/04/21           | 09 40             |               | 0.240                               | 1.000                          | 0.017                           | 0.098                                | 0.220                       |
| 73/05/05           | 16 25             |               | 1.300                               | 0.660                          | 0.022                           | 0.035                                | 0.063                       |
| 73/05/19           | 09 45             |               | 0.350                               | 0.500                          | 0.015                           | 0.138                                | 0.145                       |
| 73/06/03           | 12 45             |               | 0.450                               | 0.615                          | 0.073                           | 0.189                                | 0.230                       |
| 73/07/28           | 14 45             |               | 0.010K                              | 1.200                          | 0.046                           | 0.069                                | 0.130                       |
| 73/08/17           | 18 00             |               |                                     | 0.980                          | 0.014                           | 0.079                                | 0.164                       |
| 73/09/09           | 08 20             |               | 0.044                               | 1.050                          | 0.149                           | 0.040                                | 0.125                       |
| 73/10/06           | 13 40             |               | 0.010K                              | 0.990                          | 0.022                           | 0.019                                | 0.155                       |

K VALUE KNOWN TO BE  
LESS THAN INDICATED

25

STORET RETRIEVAL DATE 74/11/26

3604A3 LS3604A3  
42 45 00.0 077 12 30.0  
WEST RIVER  
36 7.5 RUSHVILLE  
1/CANANDAIGUA LAKE  
9 LODGETT RD BRDG ABOV RUSHVILLE STP  
11EPALES 2111204  
4 0000 FEET DEPTH

| DATE FROM TO | TIME OF DAY | DEPTH FFET | 00630 NO2AN03 N-TOTAL MG/L | 00625 TOT KJEL N MG/L | 00610 NH3-N TOTAL MG/L | 00671 PHOS-DIS ORTHO MG/L P | 00665 PHOS-TOT MG/L P |
|--------------|-------------|------------|----------------------------|-----------------------|------------------------|-----------------------------|-----------------------|
| 72/11/05     | 13 40       |            | 0.940                      | 0.500                 | 0.060                  | 0.012                       | 0.021                 |
| 72/12/02     | 13 00       |            | 3.600                      | 0.330                 | 0.017                  | 0.008                       | 0.018                 |
| 73/01/06     | 13 25       |            | 3.650                      | 0.170                 | 0.016                  | 0.007                       | 0.034                 |
| 73/02/04     | 11 35       |            | 4.100                      | 0.330                 | 0.028                  | 0.013                       | 0.045                 |
| 73/03/04     | 07 30       |            | 3.400                      | 1.470                 | 0.147                  | 0.056                       | 0.175                 |
| 73/04/07     | 10 25       |            | 3.800                      | 0.500                 | 0.031                  | 0.018                       | 0.025                 |
| 73/04/21     | 09 30       |            | 1.660                      | 0.460                 | 0.010                  | 0.006                       | 0.025                 |
| 73/05/05     | 16 15       |            | 1.980                      | 1.980                 | 0.033                  | 0.005K                      | 0.020                 |
| 73/05/19     | 09 00       |            | 1.400                      | 0.540                 | 0.016                  | 0.009                       | 0.015                 |
| 73/06/03     | 11 30       |            | 1.400                      | 0.460                 | 0.011                  | 0.017                       | 0.020                 |
| 73/07/28     | 15 10       |            | 0.042                      | 0.920                 | 0.036                  | 0.013                       | 0.100                 |
| 73/08/17     | 17 00       |            |                            | 1.600                 | 0.063                  | 0.019                       | 0.060                 |
| 73/09/09     | 08 00       |            | 0.010K                     | 1.100                 | 0.044                  | 0.015                       | 0.095                 |
| 73/10/06     |             |            | 0.010K                     | 1.980                 | 0.030                  | 0.013                       |                       |

K VALUE KNOWN TO BE  
LESS THAN INDICATED

STORET RETRIEVAL DATE 74/11/26

360481  
42 44 30.0 077 20 30.0  
SENeca PT GULLY  
36 7.5 MIDDLESEX  
T/CANANDAIGUA LAKE  
PT RD BRDG NEAR SENeca PT  
11EPALES 2111204  
4 0000 FEET DEPTH

| DATE FROM TO | TIME OF DAY | DEPTH FEET | 00630 NO <sub>2</sub> N-TOTAL MG/L | 00625 TOT KJEL N MG/L | 00610 NH <sub>3</sub> -N TOTAL MG/L | 00671 P-OS-DIS ORTHO MG/L P | 00665 PHOS-TOT MG/L P |
|--------------|-------------|------------|------------------------------------|-----------------------|-------------------------------------|-----------------------------|-----------------------|
| 72/11/05     | 15 00       |            | 0.061                              | 0.200                 | 0.180                               | 0.007                       | 0.008                 |
| 72/12/02     | 14 28       |            | 0.650                              | 0.180                 | 0.005K                              | 0.006                       | 0.020                 |
| 73/01/06     | 14 40       |            | 0.740                              | 0.100K                | 0.010                               | 0.005K                      | 0.013                 |
| 73/02/04     | 13 20       |            | 0.700                              | 0.100K                | 0.005K                              | 0.017                       | 0.030                 |
| 73/03/04     | 09 40       |            | 0.740                              | 1.200                 | 0.044                               | 0.014                       | 0.190                 |
| 73/04/07     | 12 15       |            | 0.880                              | 0.160                 | 0.017                               | 0.012                       | 0.020                 |
| 73/04/21     | 10 30       |            | 0.510                              | 0.160                 | 0.007                               | 0.005K                      | 0.007                 |
| 73/05/05     | 17 15       |            | 0.315                              | 1.050                 | 0.030                               | 0.005K                      | 0.010                 |
| 73/05/19     | 10 25       |            | 0.300                              | 0.200                 | 0.008                               | 0.017                       | 0.025                 |
| 73/06/03     | 13 50       |            | 0.378                              | 0.420                 | 0.017                               | 0.013                       | 0.015                 |
| 73/07/28     | 14 10       |            | 0.080                              | 0.150                 | 0.020                               | 0.005K                      | 0.010                 |
| 73/08/17     | 19 00       |            |                                    | 0.420                 | 0.022                               | 0.009                       | 0.015                 |
| 73/09/09     | 10 20       |            | 0.094                              | 0.400                 | 0.031                               | 0.009                       | 0.010                 |

K VALUE KNOWN TO BE  
LESS THAN INDICATED

STORET RETRIEVAL DATE 74/11/26

3494C1 LS3604C1  
42 43 30.0 0 77 19 30.0  
UNNAMED STREAM  
36 7.5 MIDDLESEX  
T/CANANDAIGUA LAKE  
EAST LAKE RD HRDG IN VINE VALLEY  
11EPALES 2111204  
4 0000 FEET DEPTH

| DATE FROM TO | TIME OF DAY | DEPTH FEET | 00630 NO2&NO3 N-TOTAL MG/L | 00625 TOT KJEL N MG/L | 00610 NH3-N TOTAL MG/L | 00671 PHOS-NIS OPTHO MG/L P | 00665 PHOS-TOT MG/L P |
|--------------|-------------|------------|----------------------------|-----------------------|------------------------|-----------------------------|-----------------------|
| 72/11/05     | 14 00       |            | 0.550                      | 0.250                 | 0.037                  | 0.007                       | 0.012                 |
| 72/12/02     | 13 25       |            | 1.700                      | 0.200                 | 0.006                  | 0.010                       | 0.016                 |
| 73/01/06     | 13 45       |            | 1.520                      | 0.100K                | 0.006                  | 0.009                       | 0.015                 |
| 73/02/04     | 12 00       |            | 2.100                      | 0.200                 | 0.006                  | 0.011                       | 0.025                 |
| 73/03/04     | 08 15       |            | 2.400                      | 0.430                 | 0.058                  | 0.050                       | 0.145                 |
| 73/04/07     | 10 55       |            | 0.505                      | 0.240                 | 0.011                  | 0.011                       | 0.039                 |
| 73/04/21     | 10 00       |            | 0.820                      | 0.250                 | 0.009                  | 0.012                       | 0.025                 |
| 73/05/05     | 16 35       |            | 0.980                      | 1.900                 | 0.360                  | 0.210                       | 0.270                 |
| 73/05/19     | 09 15       |            | 0.010K                     | 0.310                 | 0.067                  | 0.056                       | 0.070                 |
| 73/06/03     | 12 20       |            | 0.760                      | 0.460                 | 0.017                  | 0.037                       | 0.055                 |
| 73/07/24     | 14 52       |            | 0.147                      | 0.460                 | 0.030                  | 0.074                       | 0.090                 |
| 73/08/17     | 17 25       |            |                            | 1.150                 | 0.020                  | 0.050                       | 0.060                 |
| 73/09/09     | 08 45       |            | 0.048                      | 0.780                 | 0.054                  | 0.046                       | 0.050                 |
| 73/10/06     | 13 30       |            | 0.010K                     | 0.560                 | 0.126                  | 0.027                       | 0.040                 |

K VALUE KNOWN TO BE  
LESS THAN INDICATED

STREET RETRIEVAL DATE 74/11/26

360401 LS360401  
42 47 00.0 077 19 00.0  
HAYNES GULLY  
76 7.5 CANANDAIG LK  
T/CANANDAIGUA LAKE  
WEST LAKE RD RDG NEAR FOSTER POINT  
11EPALFS 2111204  
4 0000 FEET DEPTH

| DATE FROM TO | TIME OF DAY | DEPTH FEET | 00630 NO <sub>3</sub> -N-TOTAL MG/L | 00625 TOT KJEL N MG/L | 00610 NH <sub>3</sub> -N TOTAL MG/L | 00671 PHOS-DIS UPTMO MG/L P | 00665 PHOS-TOT MG/L P |
|--------------|-------------|------------|-------------------------------------|-----------------------|-------------------------------------|-----------------------------|-----------------------|
| 72/11/05     | 15 20       |            | 0.059                               | 0.150                 | 0.058                               | 0.008                       | 0.010                 |
| 72/12/02     | 14 40       |            | 0.450                               | 0.330                 | 0.012                               | 0.010                       | 0.012                 |
| 73/01/06     | 15 35       |            | 0.530                               | 0.250                 | 0.015                               | 0.008                       | 0.011                 |
| 73/02/04     | 13 40       |            | 0.570                               | 0.170                 | 0.006                               | 0.008                       | 0.020                 |
| 73/03/04     | 10 00       |            | 0.590                               | 0.540                 | 0.028                               | 0.017                       | 0.129                 |
| 73/04/07     | 12 25       |            | 1.620                               | 0.185                 | 0.019                               | 0.014                       | 0.020                 |
| 73/04/21     | 19 40       |            | 0.220                               | 0.130                 | 0.005K                              | 0.007                       | 0.010                 |
| 73/05/05     | 17 25       |            | 0.135                               | 1.720                 | 0.052                               | 0.008                       | 0.015                 |
| 73/05/19     | 10 30       |            | 0.011                               | 0.100K                | 0.006                               | 0.010                       | 0.010                 |
| 73/06/03     | 14 20       |            | 0.252                               | 0.170                 | 0.005K                              | 0.009                       | 0.010                 |
| 73/07/28     | 13 58       |            | 0.520                               | 0.420                 | 0.018                               | 0.009                       | 0.015                 |
| 73/08/17     | 19 20       |            |                                     | 0.310                 | 0.015                               | 0.018                       | 0.025                 |
| 73/09/09     | 19 40       |            | 0.840                               | 0.420                 | 0.025                               | 0.015                       | 0.015                 |
| 73/10/06     | 15 00       |            | 0.770                               | 0.420                 | 0.054                               | 0.005K                      | 0.015                 |

K VALUE KNOWN TO 4F  
LESS THAN INDICATED

STORET RETRIEVAL DATE 74/11/26

3604E1 LS3604E1  
42 48 00.0 077 18 00.0  
MENTETH GULLY  
36 7.5 CANANDAIGUA  
T/CANANDAIGUA LAKE  
WEST LAKE RD BRDG NEAR MENTETH POINT  
11EPALES 2111204  
4 0000 FEET DEPTH

| DATE<br>FROM<br>TO | TIME<br>OF<br>DAY | DEPTH<br>FEET | 00630<br>NO2-N<br>TOTAL<br>MG/L | 00625<br>TOT N<br>MG/L | 00610<br>NH3-N<br>TOTAL<br>MG/L | 00671<br>PHOS-DIS<br>OPTHO<br>MG/L P | 00665<br>PHOS-TOT<br>MG/L P |
|--------------------|-------------------|---------------|---------------------------------|------------------------|---------------------------------|--------------------------------------|-----------------------------|
| 72/11/05           | 15 55             |               | 0.302                           | 0.300                  | 0.110                           | 0.005                                | 0.006                       |
| 72/12/02           | 14 45             |               | 0.930                           | 0.120                  | 0.005K                          | 0.007                                | 0.004                       |
| 73/01/06           | 15 15             |               | 1.260                           | 0.140                  | 0.005K                          | 0.007                                | 0.010                       |
| 73/02/04           | 13 50             |               | 0.840                           | 0.250                  | 0.013                           | 0.006                                | 0.015                       |
| 73/03/04           | 10 10             |               | 0.870                           | 0.720                  | 0.023                           | 0.013                                | 0.115                       |
| 73/04/07           | 13 00             |               | 0.900                           | 0.190                  | 0.027                           | 0.011                                | 0.015                       |
| 73/04/21           | 10 45             |               | 0.800                           | 0.560                  | 0.006                           | 0.005K                               | 0.005K                      |
| 73/05/05           | 17 35             |               | 0.231                           | 0.440                  | 0.018                           | 0.005K                               | 0.010                       |
| 73/05/19           | 10 15             |               | 0.110                           | 0.150                  | 0.005K                          | 0.005K                               | 0.005K                      |
| 73/06/03           | 14 40             |               | 0.410                           | 0.540                  | 0.015                           | 0.007                                | 0.015                       |
| 73/07/28           | 13 55             |               | 0.300                           | 0.290                  | 0.014                           | 0.005K                               | 0.005K                      |
| 73/08/17           | 19 30             |               |                                 | 0.420                  | 0.036                           | 0.007                                | 0.010                       |
| 73/09/09           | 11 00             |               | 0.066                           | 0.460                  | 0.033                           | 0.004                                | 0.006                       |
| 73/10/04           | 11 40             |               | 0.024                           | 0.300                  | 0.031                           | 0.005K                               | 0.005K                      |

K VALUE KNOWN TO 25  
LESS THAN INDICATED

STORET RETRIEVAL DATE 74/11/26

1604F1 LS3604F1  
42 52 30.0 077 14 30.0  
FEEDER CANAL  
36 7.5 CANANDAIGUA  
O/CANANDAIGUA LAKE  
ST HWY 20 RDG NEAR KERSHAWPARK  
11EPALES 2111204  
4 0000 FEET DEPTH

| DATE<br>FROM<br>TO | TIME OF<br>DAY | DEPTH<br>FEET | 00630<br>NO2&NO3<br>N-TOTAL<br>MG/L | 00625<br>TOT KJFL<br>N<br>MG/L | 00610<br>NH3-N<br>TOTAL<br>MG/L | 00671<br>PHOS-DIS<br>ORTHO<br>MG/L P | 00665<br>PHOS-TOT<br>MG/L P |
|--------------------|----------------|---------------|-------------------------------------|--------------------------------|---------------------------------|--------------------------------------|-----------------------------|
| 72/11/05           | 13 00          |               | 0.450                               | 0.500                          | 0.130                           | 0.005K                               | 0.010                       |
| 72/12/02           | 14 55          |               | 0.390                               | 0.210                          | 0.005K                          | 0.005K                               | 0.007                       |
| 73/01/06           | 14 15          |               | 0.440                               | 0.210                          | 0.007                           | 0.005K                               | 0.008                       |
| 73/02/04           | 14 15          |               | 0.550                               | 0.320                          | 0.005K                          | 0.005K                               | 0.020                       |
| 73/03/04           | 10 30          |               | 0.460                               | 0.250                          | 0.009                           | 0.005K                               | 0.010                       |
| 73/04/07           | 13 10          |               | 0.520                               | 0.240                          | 0.032                           | 0.006                                | 0.015                       |
| 73/04/21           | 13 00          |               | 0.370                               | 0.350                          | 0.008                           | 0.005K                               | 0.015                       |
| 73/05/05           | 17 45          |               | 0.357                               | 0.870                          | 0.028                           | 0.005K                               | 0.015                       |
| 73/05/19           | 11 00          |               | 0.026                               | 0.300                          | 0.011                           | 0.005K                               | 0.010                       |
| 73/06/03           | 15 00          |               | 0.273                               | 0.380                          | 0.008                           | 0.007                                | 0.010                       |
| 73/07/24           | 13 35          |               | 0.069                               | 0.480                          | 0.023                           | 0.005K                               | 0.020                       |
| 73/08/17           | 19 59          |               |                                     | 0.380                          | 0.020                           | 0.005K                               | 0.015                       |
| 73/09/09           | 11 30          |               | 0.033                               | 0.560                          | 0.065                           | 0.006                                | 0.010                       |
| 73/10/06           | 15 20          |               | 0.054                               | 0.120                          | 0.062                           | 0.005K                               | 0.010                       |

K VALUE KNOWN TO BE  
LESS THAN INDICATED

STORET RETRIEVAL DATE 74/11/26

3404G1 LS3404G1  
42 53 30.0 077 15 30.0  
CANANDAIGUA OUTLET  
34 7.5 CANANDAIGUA  
0/CANANDAIGUA LAKE  
BWDG .75 MI E OF CANANDAIGUA  
11EPALES 2111204  
4 0000 FEET DEPTH

| DATE FROM TO | TIME OF DAY | DEPTH FEET | 00630 NO <sub>3</sub> -N-TOTAL MG/L | 00625 TOT KJEL N MG/L | 00671 PHOS-DIS ORTHO MG/L P | 00665 PHOS-TOT MG/L P |
|--------------|-------------|------------|-------------------------------------|-----------------------|-----------------------------|-----------------------|
| 72/11/05     | 13 00       |            | 0.160                               | 0.450                 | 0.005K                      | 0.030                 |
| 72/12/02     | 14 59       |            | 0.370                               | 0.160                 | 0.005K                      | 0.007                 |
| 73/01/06     | 16 30       |            | 0.400                               | 0.210                 | 0.005K                      | 0.006                 |
| 73/02/04     | 14 25       |            | 0.440                               | 0.260                 | 0.005K                      | 0.015                 |
| 73/03/04     | 10 40       |            | 0.380                               | 0.350                 | 0.005K                      | 0.015                 |
| 73/04/07     | 13 15       |            | 0.357                               | 0.260                 | 0.005K                      | 0.015                 |
| 73/04/21     | 11 20       |            | 0.370                               | 0.250                 | 0.005K                      | 0.010                 |
| 73/05/05     | 14 00       |            | 0.336                               | 1.200                 | 0.005K                      | 0.015                 |
| 73/05/19     | 11 10       |            | 0.320                               | 0.290                 | 0.007                       | 0.010                 |
| 73/05/03     | 15 20       |            | 0.270                               | 0.350                 | 0.007                       | 0.015                 |
| 73/07/24     | 13 30       |            | 0.010K                              | 0.620                 | 0.005K                      | 0.060                 |
| 73/08/17     | 20 00       |            |                                     | 1.150                 | 0.011                       | 0.080                 |
| 73/09/09     | 11 45       |            | 0.020                               | 0.600                 | 0.006                       | 0.025                 |
| 73/10/06     | 15 40       |            | 0.023                               | 0.270                 | 0.009                       | 0.045                 |

K VALUE KNOWN TO BE  
LESS THAN INDICATED

STOPET RETRIEVAL DATE 74/11/26

360441 LS360441  
42 39 00.0 077 22 30.0  
NAPLES CREEK  
36 7.5 MIDDLESEX  
T/CANANDAIGUA LAKE  
PARISH FLAT RD 500 FT SE OF NY 21  
11EPALES 2111204  
4 0000 FEET DEPTH

| DATE FROM TO | TIME OF DAY | DEPTH FEET | 00630<br>NH <sub>3</sub> -N<br>N-TOTAL<br>MG/L | 00625<br>TOT KJEL<br>N<br>MG/L | 00610<br>NH <sub>3</sub> -N<br>TOTAL<br>MG/L | 00671<br>PHOS-NIS<br>ORTHO<br>MG/L P | 00665<br>PHOS-TOT<br>MG/L P |
|--------------|-------------|------------|------------------------------------------------|--------------------------------|----------------------------------------------|--------------------------------------|-----------------------------|
| 72/11/05     | 14 00       |            | 0.760                                          | 0.200                          | 0.110                                        | 0.009                                | 0.023                       |
| 72/12/02     | 14 07       |            | 0.790                                          | 0.140                          | 0.007                                        | 0.006                                | 0.017                       |
| 73/01/06     | 14 20       |            | 0.820                                          | 0.160                          | 0.016                                        | 0.005K                               | 0.014                       |
| 73/02/04     | 13 00       |            | 0.740                                          | 0.240                          | 0.013                                        | 0.007                                | 0.045                       |
| 73/03/04     | 04 10       |            | 0.620                                          | 0.670                          | 0.022                                        | 0.007                                | 0.140                       |
| 73/04/07     | 11 30       |            | 0.640                                          | 0.180                          | 0.015                                        | 0.008                                | 0.030                       |
| 73/04/21     | 10 20       |            | 0.660                                          | 0.150                          | 0.009                                        | 0.005K                               | 0.010                       |
| 73/05/05     | 17 00       |            | 0.490                                          | 0.460                          | 0.020                                        | 0.005K                               | 0.015                       |
| 73/05/19     | 10 00       |            | 0.350                                          | 0.140                          | 0.005K                                       | 0.006                                | 0.010                       |
| 73/06/03     | 13 30       |            | 0.460                                          | 0.480                          | 0.015                                        | 0.008                                | 0.010                       |
| 73/07/28     | 14 30       |            | 0.610                                          | 0.290                          | 0.014                                        | 0.005K                               | 0.010                       |
| 73/08/17     | 14 40       |            |                                                | 0.690                          | 0.030                                        | 0.008                                | 0.050                       |
| 73/09/09     | 09 50       |            | 0.770                                          | 0.710                          | 0.023                                        | 0.010                                | 0.015                       |
| 73/10/06     | 14 20       |            | 0.560                                          | 0.100K                         | 0.028                                        | 0.005K                               | 0.020                       |

K VALUE KNOWN TO BE  
LESS THAN INDICATED

33